

DU PONT

PAINTS, VARNISHES, DUCO

for Every Household
and Industrial Use

Du Pont Prepared Paint
For all outside painting

Flat Wall Paint
For interior walls and woodwork.

Barn and Roof Paint
An economical paint for farm use.

Flowkote Enamel
"Like Porcelain"—for interior
or exterior use.

Cement and Stucco Coating
Protects and beautifies cement,
stucco and brick surfaces.

Shingle Stain
For preserving wood shingles.

Motor Truck and Wagon Enamel Paint
A high gloss, quick drying
enamel paint.

Auto Finishes
For renewing the used car.

Wire Screen Paint
Prevent screens from rusting.



*The du Pont Chemical
Engineer—symbol of
progress and leader-
ship in the manufac-
ture of products based
on Chemistry.*

Floor and Deck Enamel Paint
For wood or concrete floors,
exterior or interior.

Duco
For hundreds of home uses.

Colored Enamel
For furniture and household
articles.

Black Jack Enamel
A general utility black enamel.

Tufcote Varnish Stain
For floors, furniture and wood-
work.

Penetrating Stain

Acid Stain

Oil Stain

Bring out the full beauty of the
grain on new wood.

Wheeler's Wood Fillers
For new floors and woodwork.

Du Pont Varnishes:
(The famous 'yellow can line')

Supremis
The first varnish made espe-
cially for floors.

Shipoleum
For interior woodwork.

Navalite (spar)
For all outside use.

Chi-Vo
For rubbed effect.

Hyperion Finish
For fine furniture.

E. I. du Pont de Nemours & Co., Inc.

Paint and Varnish Division

PHILADELPHIA

CHICAGO BOSTON NEWARK

SAN FRANCISCO

DU PONT

Flat Wall Paint

*A Sanitary Washable Finish
for Walls & Woodwork*





FLAT WALL PAINT

Du Pont Flat Wall Paint is an oil paint. The prime pigment used is lithopone, manufactured in our own plants, insuring quality and uniformity. No lead or poisonous pigment of any kind is used. This product should not be confused with calcimine or cold water paints. It may be readily washed, and because of its sanitary features is especially desirable as a wall finish for apartments, hotels, offices, hospitals and homes.

On the average it will spread 400 square feet of surface to the gallon, two coats, or 600 to 700 square feet, one coat.

White supplied in half-pint, pint, quart, half-gallon, and gallon cans.

Colors supplied in pint, quart, half-gallon, and gallon cans.

The most satisfactory results are obtained by employing a reliable painting contractor.

ELASTIC WALL PRIMER

Du Pont Elastic Wall Primer is the proper undercoat for flat wall paints. It is a high grade varnish size which stops all suction on plaster, cement or brick surfaces and also prevents undue absorption of the subsequent coats of paint.

Supplied in quart, half-gallon, and gallon cans.



DIRECTIONS

New or Old Unpainted Walls, smooth hard-coated or rough sand finish

Apply a first coat of Du Pont Flat Wall Paint of the desired shade to which has been added Elastic Wall Primer in the proportion of three parts of Flat Wall Paint to one part of Elastic Wall Primer. Finish with a second coat of Du Pont Flat Wall Paint as received.

NOTE—Cracks and crevices in smooth walls should be filled with plaster of Paris before painting. On rough walls, fill with material same as originally used on the walls.

OLD PAINTED WALLS

Smooth or rough walls previously painted with oil paint, any washable paint or Du Pont Flat Wall Paint

Clean walls thoroughly. All cracks or holes in smooth walls must be filled with plaster of Paris, or in rough walls with material same as originally used. Allow to dry until thoroughly hard. Coat these spots with Elastic Wall Primer to which has been added Du Pont Flat Wall Paint to approximately match the desired shade. A good combination is three parts Elastic Wall Primer to one part Flat Wall Paint. When thoroughly dry, follow with one or two coats of Du Pont Flat Wall Paint of package consistency, allowing thorough drying between coats.

Previously painted walls in good condition, where the color is not to be changed, should be given one coat only of the same shade of Du Pont Flat Wall Paint as it comes from the package.



FLAT WALL PAINT

For interior walls, ceilings and woodwork, Du Pont Flat Wall Paint is the ideal coating. It produces a smooth, velvety surface which is washable and sanitary.


The variety of beautiful tints shown in this folder lend themselves to any interior decorative treatment and innumerable attractive color combinations are obtainable with these colors. Du Pont Flat Wall Paint may also be used in producing an endless variety of stippled or mottled effects.

Du Pont Flat Wall Paint gives satisfactory results on plaster, wall board, or woodwork. Being an oil paint, it may be washed repeatedly.

DU PONT Flat Wall Paint is an excellent flat finish for radiators which may be painted to conform to the color scheme of the room. Tests have shown that radiators painted with a non-metallic paint show a marked improvement in heat radiation.

In addition to being used in residences, du Pont Flat Wall Paint is specified by leading architects for offices, hospitals and public buildings.

Where a gloss finish is desired on interior walls or woodwork du Pont Colored Enamels or du Pont Floor and Deck Enamel Paint will give excellent results.



No. 11 LIGHT BUFF



No. 23 LIGHT TAN



No. 58 LIGHT ROSE TINT



No. 26 BLUE TINT



Ceiling White
Side Wall No. 13




Ceiling White
Side Wall No. 16



Ceiling No. 15
Side Wall No. 12



Ceiling No. 11
Side Wall No. 25



No. 13 IVORY



No. 3 CREAM



No. 16 YELLOW TINT



No. 27 LIGHT BLUE



Ceiling No. 26
Side Wall No. 3




Ceiling No. 15
Side Wall No. 58



Ceiling No. 3
Side Wall No. 11



Ceiling No. 13
Side Wall No. 26



No. 12 GRAY




No. 15 FRENCH GRAY




No. 32 GREEN TINT



No. 25 DARK TAN



Ceiling White
Side Wall No. 15



Ceiling No. 15
Side Wall No. 27



Ceiling No. 11
Side Wall No. 32



Ceiling No. 3
Side Wall No. 23



FL

Du Po
The prin
factured
and unifo
of any k
be confus
It may b
sanitary
wall fini
hospitals

On th
feet of su
to 700 sc

White
half-gall

Colors
and gall

The n
by empl

ELA

Du P
underco
grade v
plaster,
vents un
of paint

Supplea in quart, half gallon,
cans.



DIRECTIONS

New or Old Unpainted Walls, smooth

Digitized by



ASSOCIATION
FOR
PRESERVATION
TECHNOLOGY,
INTERNATIONAL
www.apti.org

BUILDING
TECHNOLOGY
HERITAGE
LIBRARY

<https://archive.org/details/buildingtechnologyheritagelibrary>

From the collection of:

Jablonski Building Conservation
www.jbconservation.com

ation, where the color is not to be
changed, should be given one coat only
of the same shade of Du Pont Flat Wall
Paint as it comes from the package.